



# SUPER Printing

INFO#	Company/Website	Product Name	Ink Type	Ink Channels	Resolution (dpi)	Maximum Speed (sf/h)		Maximum Width		Pricing
						Production	Quality	Inches	Meters	
130	Agfa agfagraphics.us	Jeti Mira MG2716 HS	UV LED Curable	6+W	920x1,200	893	462	106	2.69	CM
		Jeti Mira MG2732 HS	UV LED Curable	6+W	920x1,200	893	462	106	2.69	CM
		Jeti Tauro H2500 LED	UV LED Curable	6, 6+4W, 6+8W, or 6+4W2P	725x1,200	1,485	743	100	2.54	CM
		Jeti Tauro H3300 LED 4c	UV LED Curable	4, 4+12W, 4+8W4P	725x1,200	3,250	2,433	130	3.3	CM
		Jeti Tauro H3300 LED 6c	UV LED Curable	6, 6+12W, 6+8W4P	725x1,200	2,433	1,216	130	3.3	CM
		Anapurna FB2540i LED	UV LED Curable	6+W	720x1,440	527	291	100	2.54	CM
		Anapurna H2500i LED	UV LED Curable	6+W	720x1,400	614	334	98	2.5	CM
		Anapurna H3200i LED	UV LED Curable	6+W	720x1,400	689	366	126	3.2	CM
		Anapurna RTR3200i LED	UV LED Curable	4+W or 6	720x1,440	700	355	126	3.2	CM
		Oberon RTR3300	UV LED Curable	4+W or 6	900x600	915	463	130	3.3	CM
131	Canon Solutions America, Inc. csa.canon.com	Arizona 318 GL	UV-Curable	4+W	1,440	131	90	98.4	2.5	CM
		Arizona 365 GT	UV-Curable	5	1,440	239	165	98.4	2.5	CM
		Arizona 6160 XTS	UV-Curable	6	1,400	1,076	775	98.4	2.5	CM
		Arizona 6170 XTS	UV-Curable	7	1,400	1,076	775	98.4	2.5	CM
		Arizona 6160 HFV	UV-Curable	6	1,400	1,076	775	98.4	2.5	CM
		Arizona 6170 HFV	UV-Curable	7	1,400	1,076	775	98.4	2.5	CM
		Arizona 1240 GT	UV-Curable	4	1,400	270	153	98.4	2.5	CM
		Arizona 1240 XT	UV-Curable	4	1,400	280	157	98.4	2.5	CM
		Arizona 1260 GT	UV-Curable	6	1,400	270	153	98.4	2.5	CM
		Arizona 1260 XT	UV-Curable	6	1,400	280	157	98.4	2.5	CM
		Arizona 1280 GT	UV-Curable	8	1,400	270	153	98.4	2.5	CM
		Arizona 1280 XT	UV-Curable	8	1,400	280	157	98.4	2.5	CM
		Arizona 1340 GT	UV-Curable	4	1,400	271	157	98.4	2.5	CM
		Arizona 1340 XT	UV-Curable	4	1,400	279	162	98.4	2.5	CM
		Arizona 1360 GT	UV-Curable	6	1,400	271	157	98.4	2.5	CM
		Arizona 1360 XT	UV-Curable	6	1,400	279	162	98.4	2.5	CM
		Arizona 1380 GT	UV-Curable	8	1,400	271	157	98.4	2.5	CM
		Arizona 1380 XT	UV-Curable	8	1,400	279	162	98.4	2.5	CM
		Arizona 2260 GT	UV-Curable	6	1,400	473	280	98.4	2.5	CM
		Arizona 2260 XT	UV-Curable	6	1,400	514	297	98.4	2.5	CM
Arizona 2280 GT	UV-Curable	8	1,400	473	280	98.4	2.5	CM		
Arizona 2280 XT	UV-Curable	8	1,400	514	297	98.4	2.5	CM		
Arizona 2340 GTF	UV-Curable	4	1,400	473	280	98.4	2.5	CM		
Arizona 2340 XTF	UV-Curable	4	1,400	514	297	98.4	2.5	CM		
Arizona 2360 GTF	UV-Curable	6	1,400	473	280	98.4	2.5	CM		
Arizona 2360 XTF	UV-Curable	6	1,400	514	297	98.4	2.5	CM		
Arizona 2380 GTF	UV-Curable	8	1,400	473	280	98.4	2.5	CM		
Arizona 2380 XTF	UV-Curable	8	1,400	514	297	98.4	2.5	CM		
132	CET Color cetcolor.com	Q6-Series 500	UV-Curable	6+W	1,200x1,200	832	286	96	2.5	CM
		Q6-Series 500h	UV-Curable	6+W	1,200x1,200	650	249	98	2.5	CM
		Q6-Series 500 3 Row	UV-Curable	6+W+V	1,200x1,200	845	299	120	2.5	CM
		Q6-Series 1000	UV-Curable	6+W	1,200x1,200	820	320	120	3.2	CM
		Q6-Series 1000h	UV-Curable	6+W	1,200x1,200	949	397	120	3.2	CM
		K2-series 500	UV-Curable	6+W	1,200x1,200	1,120	480	96	2.5	CM
		K2-series 1000	UV-Curable	6+W	1,200x1,200	1,400	651	120	2.5	CM
		K2-series 1000L	UV-Curable	4+W	1,200x1,200	3,000	1,310	120	3.2	CM
133	d.gen International dgen.com	Teleios Grande H6	DS, PIG, REA	6	2,400	1,520	790	130	3.3	CM
		Teleios Grande H5	DS, PIG, REA	4 or 8	2,400	3,200	1,200	130	3.3	CM
134	DGI dgi-net.com	VE-3204X	ES	4	1,440	753	538	130	3.3	CM
		FT-3204X	DS, DIS	4, 6, or 8	1,440	753	485	130	3.3	CM
		FH-3204	DS, DIS	4 or 6	1,800	1,238	1,012	126	3.2	CM

# ROWWIDE

## Options



INFO#	Company/Website	Product Name	Ink Type	Ink Channels	Resolution (dpi)	Maximum Speed (sf/h)		Maximum Width		Pricing
						Production	Quality	Inches	Meters	
135	Digifab Systems Inc digifab.com	StampaJet XP-104	AQ: DIS, SUB, PIG	8	1,440	1,160	360	104	2.6	\$84,900
		StampaJet K2-350	AQ: DS, PIG	4	600x1,200	2,854	850	126	3.2	\$119,000
		StampaJet K4-330	AQ: DS, PIG	8	600x1,200	3,414	850	126	3.2	\$139,900
136	Durst Image Technology US LLC durstus.com	StampaJet K2-330TX	AQ: DS, PIG, DIS, REA, A	8	600x1,200	3,414	850	128	3.2	CM
		Rho 2500	UV-Curable	8	1,000	12,055	4,520	98	2.5	CM
		P5 350	UV LED	6	1,200	3,850	1,883	138	3.5	CM
		Rho 512R Plus	UV-Curable	8	1,200	4,300	1,635	196	5	CM
		Rho 312R Plus	UV-Curable	8	1,200	3,250	1,375	126	3.2	CM
137	EFI efi.com	WT 250	Durst Water Technology	6	1,000	3,650	2,635	98	2.5	CM
		Rhotex 325	WB DIS DS	8	800	4,130	1,800	126	3.2	CM
		Quantum	UV	7+W	1,200	2,687	2687	120/196	3/5	CM
		Quantum LX	UV LED	8	1,200	CM	CM	120/195	3/5	CM
		Pro 32r	UV LED	4+W or 4+Overcoat	847	2,756	CM	126	3.2	CM
		VUTEK 32h	UV LED	8+W	1,000	2,454	900	126	3.2	CM
		VUTEK 5r+	UV LED	7+W	1,200	5,156	CM	198	5	CM
		VUTEK 3r+	UV LED	7+W	1,200	4,284	CM	138	3.5	CM
		VUTEK D3r	UV LED	4+W+Overcoat	1,200	2,196	CM	138	3.5	CM
		VUTEK D5r	UV LED	4+W+Overcoat	1,200	2,626	CM	205	5.2	CM
138	FLORA/American Printing Systems florusa.net	VUTEK h3	UV LED	8+W	1,200	CM	CM	126	3.2	CM
		VUTEK h5	UV LED	8+W	1,200	CM	CM	126	3.2	CM
		VUTEK LX3 Pro	UV LED	8+W	1,000	3,400	2,300	126	3.2	CM
		VUTEK GS3250X	UV-Curable	8+W	1,000	2,400	600	126.6	3.2	CM
		VUTEK GS3250LXr	UV LED	6	1,000	1,200	600	126.5	3.2	CM
		VUTEK GS5250LXr Pro	UV LED	8+W	1,000	2,800	700	204	5.1	CM
		VUTEK GS5500LXr Pro	UV LED	8 or 8+W	1,000	2,800	600	196.8	5	CM
		VUTEK H5125 Pro	UV-Curable	4	600	4,500	750	126.5	3.2	CM
		VUTEK FabriVU 520	AQ DIS Dye	4	2,400	4,800	1,700	205	5.2	CM
		VUTEK FabriVU 340/340i	AQ DIS Dye	4	2,400	5,381	1,776	133	3.4	CM
139	Fujifilm NA Corp., Graphic Systems Div. fujifilminkjet.com	FLORA PP2512uvuv - R2R option	UV-Curable	4 to 16	720x1,440	990	CM	96	2.4	CM
		FLORA PP3220UV 6.5x10'	UV-Curable	4 to 16	720x1,440	990	CM	120	3	CM
		FLORA Xtra2512UV 4x8"	UV LED	4 to 30	720x1,440	1,421	CM	96	2.4	CM
		FLORA Xtra3220UV 6.5x10'	UV LED	4 to 30	720x1,440	1,421	CM	120	3	CM
		FLORA Xtra3300UV R2R 10.5'	UV LED	4 to 18	720x1,440	2,000	CM	126	3.2	CM
		FLORA Xtra3300L UV R2R 10.5"	UV LED	4 to 18	720x1,440	1,000	CM	126	3.2	CM
		Acuity LED 3200R	UV LED	8	1,200	1,184	CM	126	3.2	CM
140	Gandy Digital gandydigital.com	Acuity Select 20 X2	UV	4, 6, or 8	1,200	368	153	120	3	CM
		Acuity Select HS 30 X2	UV	8	1,200	696	280	120	3	CM
		Acuity LED 40 X2	UV	4, 6 or 8	1,200	568	162	120	3	CM
		Acuity F	UV	6 or 7	1,200	1,668	775	120	3	CM
		Acuity Ultra Series	UV	6, 6+WW, 8	1,200	4,327	2540	202	5.13	CM
		Inca OnsetX1-LT	UV	4 to 7	1,200	2,152	2,152	126	3.2	CM
		Inca OnsetX1	UV	4 to 9	1,200	4,304	3,336	126	3.2	CM
		Inca OnsetX2	UV	4 to 14	1,200	6,889	5,382	126	3.2	CM
		Inca OnsetX2 HS	UV	4 to 14	1,200	8,762	6,657	126	3.2	CM
		Inca OnsetX3	UV	4 to 14	1,200	9,688	8,611	126	3.2	CM
141	Gandy Digital gandydigital.com	Inca OnsetX3 HS	UV	4 to 14	1,200	15,597	11,733	126	3.2	CM
		SpyderX	UV	6 or 6+WW	1,200	1,981	732	126	3.2	CM
		Pred8tor	UV	4+W, 6+W, or 8	900x720	1,410	480	96	2.5	\$275,000
		Domin8tor	UV	4+W, 6+W, or 8	900x720	1,650	576	120	3	\$325,000
		Softjet4 - 3312	WB	4 or 6	900x600	800	430	130	3.3	\$225,000
		Softjet4 - 3308	WB	4 or 6	900x600	650	300	102	2.6	\$125,000
		Fascin8tor	UV	4+W, 6+W, or 8	900x720	2,500	1,250	197	5	\$325,000
142	Gandy Digital gandydigital.com	Termin8tor	ES/MS	4	600x1,200	2,200	700	126	3.2	\$125,000
		Softjet5000	WB	4 or 6	600x1,200	3,444	1,292	209	5.3	CM

### PRINTERS OVER 95" IN WIDTH

**KEY**

- A = Acid
- AQ = Aqueous
- C = Clear
- CM = Contact Manufacturer
- DIS = Disperse
- DS = Dye-Sublimation
- ES = Eco-Solvent
- Lc = Light Cyan
- Lm = Light Magenta
- LX = Latex
- MS = Mild-Solvent
- N/A = Not Applicable
- O = Optimizer
- P = Primer
- PIG = Pigment
- REA = Reactive
- SUB = Sublimation
- V = Varnish
- W = White
- WB = Water-Based

*All printers utilize piezoelectric drop on demand technology except when noted with \* which denotes thermal technology.*

# SUPERWIDE

## Printing Options

### PRINTERS OVER 95" IN WIDTH

#### KEY

- A = Acid
  - AQ = Aqueous
  - C = Clear
  - CM = Contact Manufacturer
  - DIS = Disperse
  - DS = Dye-Sublimation
  - ES = Eco-Solvent
  - Lc = Light Cyan
  - Lm = Light Magenta
  - LX = Latex
  - MS = Mild-Solvent
  - N/A = Not Applicable
  - O = Optimizer
  - P = Primer
  - PIG = Pigment
  - REA = Reactive
  - SUB = Sublimation
  - V = Varnish
  - W = White
  - WB = Water-Based
- All printers utilize piezoelectric drop on demand technology except when noted with \* which denotes thermal technology.*

INFO#	Company/Website	Product Name	Ink Type	Ink Channels	Resolution (dpi)	Maximum Speed (sf/h)		Maximum Width		Pricing
						Production	Quality	Inches	Meters	
141	Hollanders Printing Systems hollanders-ps.nl	ColorBooster 250	WB: DIS, SUB	8	900	1,290	690	99	2.52	CM
		ColorBooster 320	WB: DIS, SUB	8	900	1,290	775	127	3.22	CM
		ColorBooster DS 320	WB: DIS, SUB	CM	720	860	860	126	3.17	CM
142	HP Inc. hp.com/go/graphicarts	Latex 1500*	LX	6+0	1,200x1,200	800	N/A	126	3.2	CM
		Latex 3600*	LX	6+0	1,200x1,200	1,950	290	126	3.2	CM
		Latex R2000 Plus*	LX	6+0+Overcoat	1,200x1,200	948	496	126	3.2	CM
		Stitch S1000	DS	4	1,200x600	3,770	1,400	126	3.2	CM
		PageWide Web Press T400S	WB PIG	4	1,200	125,000	N/A	108	2.7	CM
143	Mimaki USA, Inc. mimakiusa.com	JFX200-2531	UV-LED	4+W+C, 4+Lc+Lm+W, or 4+W	1,200	269	CM	122	3.1	CM
		JFX500-2131	UV-LED	4+W or 4+W+C	1,200	645	CM	122	3.1	CM
		UVJ55-320	UV-LED	4+Lc+Lm+W	1,200	1,194	CM	128	3.25	CM
		TS500P-3200	DS	6	1,080	1,937	CM	129.9	3.3	CM
		TX500P-3200DS	SUB	6	1,080	1,399	CM	129.9	3.3	CM
144	MS Printing Solutions msitaly.com	JPK EVO	REA, A, DIS, SUB, PIG	4 to 8	600x600	10,333	5,600	126	3.2	CM
		Lario	REA, A, DIS, SUB, PIG	4 to 8	600x600	65,000	50,000	126	3.2	CM
		JP4 320	SUB	4 to 8	600x600	3,000	1,700	126	3.2	CM
145	Mutoh America, Inc. mutoh.com	ValueJet 2638X/WX	ES/AQ	4, 7, or 8	1,440	1,168	CM	104	2.6	CM
		PJ-2508UF	UV-LED	4, 5 or 6	1,200	457	CM	100	2.54	CM
146	Paradigm Imaging Group paradigmimaging.com	PIXIS 32ES	ES	4	1,440	430	215	126	3.2	\$28,500
		PIXIS 2513UV	UV	4 or 4+Lc+Lm+W	1,080x1,440	252	105	48x96	2.5	\$79,500
		PIXIS 2030UV	UV	4 or 4+Lc+Lm+W	1,080x1,440	252	105	72x120	3	\$95,500
		SID Mercury 320	ES	4 or 4+Lc+Lm	720	807	473	126	3.2	\$39,500
		SID Mercury GS 320	ES	4+Lc+Lm	1,440	979	333	126	3.2	\$64,900
		SID Titan 320	ES	4+Lc+Lm	720	419	150	126	3.2	\$32,500
		SID Titan 320 GS	ES	4+Lc+Lm	1,440	979	333	126	3.2	\$52,900
		SID Triton S 320	ES	4	2,880	473	236	126	3.2	\$31,900
147	PrinterEvolution, LLC printerevolution.com	SID EcoTech Taurus 320 ES	ES	4	2,880	366	269	126	3.2	\$18,995
		Eos 100 DS	AQ DS	8 to 12	1,200	820	440	100	3.5	CM
		Eos 126 DS	AQ DS	4 to 12	1,200	925	580	126	3.2	CM
		Kayol26 DS	AQ DS	8 to 12	1,200	870	470	126	3.2	CM
		T2600 DS	AQ DS	2 or 4	1,200	1,570	1,000	102	2.6	CM
		T3200 DS	AQ DS	2 or 4	1,200	1,700	1,100	126	3.2	CM
		D2600 DS	AQ DS	2 or 4	1,200	1,570	1,000	102	2.6	CM
		D3200 DS	AQ DS	2 or 4	1,200	1,700	1,100	126	3.2	CM
148	SCG Digital America Inc. scg-america.com	D5300 DS	AQ DS	4 or 8	1,200	2,020	1,300	208	5.3	CM
		GD3200 AE-S	ES	4, 6, or 8	1,440	430	215	128	3.2	CM
		GD3200 AE-TX	SUB	4, 6, or 8	1,440	430	215	128	3.2	CM
		SUPRAQ 3200-TX6	WB DIS SUB	6	400	CM	CM	128	3.2	CM
		GD3200 CR-UV	UV	4 or 6	1,200	161	129	128	3.2	CM
149	StratoJet USA Inc. stratojetusa.com	M3200-UV	UV	6+W	1,200	CM	CM	128	3.2	CM
		Shark FBR 2512	UV-LED Curable	4 to 8	1,200	1,300	700	96	2.5	CM
		Shark EFB 2512	UV-LED Curable	4 to 8	1,200	600	360	96	2.5	CM
		Shark FB 2532	UV-LED Curable	4 to 8	1,200	1,300	700	96	2.5	CM
		Shark FB 2512	UV-LED Curable	4 to 8	1,200	1,300	540	96	2.5	CM
		Shark II UV	UV-LED Curable	4 to 8	1,200	1,050	450	131	3.2	CM
150	swissqprint swissqprint.com	Falcon XL 3300	UV-LED Curable	9	1,200	1,442	450	131	3.2	CM
		Oryx 3	UV LED	9	1,080	700	151	98	2.5	CM
		Impala 3	UV LED	9	1,080	1,938	517	98	2.5	CM
		Nyala 3	UV LED	9	1,080	2,217	581	126	3.2	CM
		Impala 3S	UV LED	9	1,080	3,412	958	98	2.5	CM
		Nyala 3S	UV LED	9	1,080	3,982	1,087	126	3.2	CM
151	Teckwin International LLC teckwin.com	Karibu	UV LED	9	1,080	2,282	613	133	3.4	CM
		TW 3200r	UV-Curable	4, 4+W, 6, or 6+W	CM	1,689	215	125	3.2	CM
		TW 5000r	UV-Curable	4, 4+W, 6, or 6+W	CM	2,098	592	196	5	CM
		TeckPro UV3200	UV-Curable	7	800x800	990	450	130	3.3	CM
152	Vanguard Digital Printing Systems A Durst Group Company vanguarddigital.com	TS2513L	UV-Curable	6+2W	CM	CM	CM	96	2.5	CM
		VK300D-HS	UV LED Curable	10	1,800	1,980	1,500	126	3.2	CM
		VKM600T-HS	UV LED Curable	10	1,800	1,980	1,500	99	2.5	CM
		VR5D-E	UV LED Curable	10	1,800	1,960	550	99	2.5	CM
		VKR3200-HS	UV LED Curable	6	1,800	1,229	678	126	3.2	CM

